



EAN-Nr.: 4251003108200

5DL68850 80cm Head free hood, black glass

Power / Consumption

- Energy efficiency class: A
- Average energy consumption: 41.0 kW/year
- Fan efficiency class: A
- Lighting efficiency class: A
- Grease filter efficiency class: B
- Total connected load: 252 W
- Voltage: 220-240 VV

Equipment / Comfort

- Glass shade black
- For wall mounting above hobs
- Optionally exhaust air or recirculated air operation
(a starter set is required for recirculation operation)
- Fan power 4-stage
(3 power levels + 1 intensive level) adjustable via touch control with LED display
- Intensive levels with automatic reset
- Automatic fan run-on
- Electronic control
- Powerful and quiet fan
- Edge suction
- Uniform, bright illumination with 2 x 1,1 W LED lamps
- Illuminance: 200 lux
- Color temperature: 3.000 or 4.000 K
- Metal grease filter, dishwasher safe

Multicontrol

Dimensions

- Device dimensions exhaust air (HxWxD): 837-899x800x380 mm
- Device dimensions recirculation air (HxWxD): 960-1022x800x380 mm

Accessories:

Special Accessories:

- 5Z9100X1: Activated carbon filter for recirculation mode
- 5Z9100X2: Activated carbon filter-Longlife for recirculation mode
- 5Z9117X3: Shaft extension, 500mm, black
- 5Z9117X4: Shaft extension, 990mm, black

Available color options:

BLAUPUNKT

Equipment features:

Device type: head free-standing hood
 Color of the fireplace: Black
 Type of construction: wall-mounted
 Approval certificates: CE, UKCA
 Length of connection cable (cm): 150
 niche dimensions (mm): 382x800x380
 Height of the fireplace: 455 / 640 mm
 Height of the device without fireplace (mm): 382
 net weight (kg): 13,8
 Control: Touch Control
 Regulation of power levels: 3 + intensive
 Max. Fan power-extract air mode (m³/h): 590 Fan power-intensive level-recirculate air mode: 400 Max. Fan capacity-circulating air mode (m³/h): 390 Max. fan power in intensive stage-exhaust air mode (m³/h): 740
 Sound power (dB(A) re 1 pW): 62
 diameter of the exhaust air spigot (mm): 150/120
 Grease filter material: Aluminum
 Odor filter: No
 Type of air duct: Convertible
 Number of lamps (pieces): 2
 Type of lamps: LED
 Total power of lamps (W): 2x1,1
 Filter change reminder: No

Consumption and connected load:

connected load (W): 252
 Fuse rating (A): No
 Voltage (V): 220-240
 Frequency (Hz): 50-60
 Plug type: Schuko
 Type of installation: Wall
 Housing material: Painted housing Approval certificates: CE, UKCA
 Plug type: Schuko
 Dimensions of the unit, with chimney:
 Exhaust air (HxWxD): 837-899x800x380 mm
 recirculation (HxWxD): 960-1022x800x380 mm
 Dimensions of the packed unit: 88,9 x 49,9 x 57,9cm
 Net weight (kg): 13,8
 Gross weight (kg): 17,3
 Position of blower: Motor in housing
 Drainage direction: Upwards Backflow flap: Yes
 Length of connection cable (cm): 150