



Wall hood
5IS66760 - 102G60-BK

Power / Consumption

- Annual Efficiency Consumption: 232*2*361+1000=167.50kw/h
- Total connected load:232W±20%
- Voltage: 220-230V
- Sound power (dB(A) re 1 pW): 68 dB

Equipment / Comfort

- Delay Shut off modes:Yes
- Level fan output: 3 power
- control: touch control
- Filter alarm:
- light: 1 x2 W LED
- Cone size filter with 2 layers
- Power:
 - Power - exhaust air operation (m3/h): 837±50
 - Power intensive exhaust air operation (m3/h) :1094±50
 - Power-circulating air operation (m3/h):
 - Power in intensive air recirculation mode (m³/h):

Technical data and dimensions (HxWxD)

- Extraction: 160mm
- Circulation:380x305x502mm
- Device dimensions (packed): 660*655*490mm
- Net weight (kg): 15
- Gross weight (kg):18
- Chimney height (mm): 523
- Height of the unit without chimney (mm):72

Accessories:



Special accessories:

Available color options:

SS or BK



Features:

- Hood type: Wall hood
- Chimneys Colour: black power coating hood with S/S panel
- Approval certificates: Yes
- Length of connection cable (cm): 150
- Height of the chimney (mm): 523
- Height of the hood without chimney (mm): 72
- Number of lamps (pcs): 1
- Outlet diameter (mm): 160mm
- Grease filter material: S/S
- Required accessories: Flue pipe/Screws
- Special accessories:
- Type of lamps: Square shape
- Lamp power (W): 1*2W
- Grease filter type: Cone size filter with 2 layers

Consumption and connection values:

- Connected load (W): 232W
- Fuse rating (A): F5A L250V
- Voltage (V): 220-230
- Frequency (Hz): 50
- Plug type: Indian 3-pin round plug
- Housing material: S/S,glass
- Approval certificates: Yes
- Required distance between hob and hood
- Electric hob: 650-700mm,
- Gas hob: 650-700mm
- Position of the fan: motor in the casing

