



Wall hood SIS69751
Power / Consumption <ul style="list-style-type: none"> Annual Efficiency Consumption: Total connected load: 321 W Voltage: 220-230V Sound power (dB(A) re 1 pW): 68 dB
Equipment / Comfort <ul style="list-style-type: none"> Delay Shut off modes: Yes Level fan output: 3 power control: touch control Filter alarm: light: 2 x 1.5 W LED Baffle Filter
Power: <ul style="list-style-type: none"> Power - exhaust air operation (m3/h): 636.65 Power intensive exhaust air operation (m3/h): 850.11
Technical data and dimensions (HxWxD) <ul style="list-style-type: none"> Device Dimensions: 380 x 330 x 445 mm Device dimensions (packed): 958 x 710 x 590 mm Net weight (kg): 19.2 Gross weight (kg): 23.9 Chimney height (mm): 450 Height of the unit without chimney (mm): 565

EAN-Code: 4251003104509

Accessories: 
Special accessories:
Available color options:



Features: <ul style="list-style-type: none"> Hood type: Wall hood Chimneys Colour: black Approval certificates: Length of connection cable (cm): 150 Height of the chimney (mm): 500 Height of the hood without chimney (mm): 70 Number of lamps (pcs): 2 Outlet diameter (mm): 150 Grease filter material: S/S Required accessories: Flue pipe/Screws Special accessories: Type of lamps: Round shape Lamp power (W): 1.5 Grease filter type: baffle filter
Consumption and connection values: <ul style="list-style-type: none"> Connected load (W): 321 Fuse rating (A): F5A L250V Voltage (V): 220-230 Frequency (Hz): 50 Plug type: Indian 3-pin round plug Housing material: S/S, glass Approval certificates: Required distance between hob and hood Electric hob: 650-700mm Gas hob: 650-700mm Position of the fan: motor in the casing

