



EAN: 4251003107883

Wall hood
5IS66860

Power / Consumption

- Annual Efficiency Consumption: 233.6Kwh
- Total connected load: 256W
- Voltage: 220-230V
- Sound power (dB(A) re 1 pW): ≤ 72 (dB)

Equipment / Comfort

- Delay Shut off modes: Yes
- Level fan output: 3 power
- control: touch with gesture control
- Filter alarm: N/A
- light: 1*2w LED
- Filterless
- Power:
 - Power - exhaust air operation (m3/h): 8541
 - Power intensive exhaust air operation (m3/h) : 1165
 - Power-circulating air operation (m3/h):
 - Power in intensive air recirculation mode (m³/h):

Technical data and dimensions (HxWxD)

- Extraction: 150mm
- Circulation:
- Device dimensions (packed): 650x465x435
- Net weight (kg): 15.5kg
- Gross weight (kg): 17.7kg
- Chimney height (mm): 849
- Height of the unit without chimney (mm): 419

Accessories:

Special accessories:

Available color options:



Features:

- Hood type: Wall hood
- Chimneys Colour: black
- Approval certificates: power plug with ISI 2019
- Length of connection cable (cm): 150
- Height of the chimney (mm): 849
- Height of the hood without chimney (mm): 430
- Number of lamps (pcs): 2
- Outlet diameter (mm): 150mm
- Grease filter material: MS
- Required accessories: Flue pipe/Screws
- Special accessories:
- Type of lamps: Square shape
- Lamp power (W): 1.5
- Grease filter type: filterless

Consumption and connection values:

- Connected load (W): 256W
- Fuse rating (A): 10A
- Voltage (V): 220-230
- Frequency (Hz): 50
- Plug type: Indian 3-pin round plug
- Housing material: MS
- Approval certificates:
- Required distance between hob and hood: 350mm-450mm
- Position of the fan: motor in the casing