



EAN: 4251003107890

**Wall hood**  
**5IS69960**

**Power / Consumption**

- Annual Efficiency Consumption: 211.7kw/h
- Total connected load: 232
- Voltage: 220-240V
- Sound power (dB(A) re 1 pW):  $\leq 72$  (dB)

**Equipment / Comfort**

- Delay Shut off modes: Yes
- Level fan output: 3 power
- control: touch control
- Filter alarm:
- light: 2\*1.5w LED
- Filterless
- Power:
  - Power - exhaust air operation (m3/h): 700m<sup>3</sup>/h
  - Power intensive exhaust air operation (m3/h) : 850m<sup>3</sup>/h
  - Power-circulating air operation (m3/h):
  - Power in intensive air recirculation mode (m<sup>3</sup>/h):

**Technical data and dimensions (HxWxD)**

- Extraction: 150
- Circulation:
- Device dimensions (packed):975\*625\*425mm
- Net weight (kg): 18.0kg
- Gross weight (kg): 20.7kg
- Chimney height (mm): 588
- Height of the unit without chimney (mm): 223

**Accessories:**

**Special accessories:**

**Available color options:**



**Features:**

- Hood type: Wall hood
- Chimneys Colour: black
- Approval certificates:
- Length of connection cable (cm): 150
- Height of the chimney (mm):588
- Height of the hood without chimney (mm): 365
- Number of lamps (pcs): 2
- Outlet diameter (mm): 150mm
- Grease filter material: glass
- Required accessories: Flue pipe/Screws
- Special accessories:
- Type of lamps: Square shape
- Lamp power (W): 1.5
  - Grease filter type: filterless

**Consumption and connection values:**

- Connected load (W): 232W
- Fuse rating (A): 10A
- Voltage (V): 220-230
- Frequency (Hz): 50
- Plug type: Indian 3-pin round plug
- Housing material: MS
- Approval certificates:
- Required distance between hob and hood: 450mm-550mm
- Position of the fan: motor in the casing